


AX3600 WiFi6 5G NR CPE

WR862GVNM



VoLTE



Qos



Guest Network



Bulit-in Firewall

Hardware

- Mobile Communication System: Europe

5G NR	5G NR: 3GPP Release 15 NSA/SA operation, Sub-6 GHz SA/NSA Bands: n1/n3/n5/n7/n8/n20/n28/n38/n40/n41/n77/n78 DL 4 × 4 MIMO: n1/n3/n7/n38/n40/n41/n77/n78 UL 2 × 2 MIMO: n40/n41/n77/n78
LTE	LTE Category: Cat 19 LTE Bands: B1/B3/B5/B7/B8/B20/B28/B32/B38/B40/B41/B42/B43 DL 4 × 4 MIMO: B1/B3/B7/B38/B40/B41/B42
UMTS	WCDMA Bands: B1/B5/B8

- Latam/America

5G NR	5G NR: 3GPP Release 15 NSA/SA operation, Sub-6 GHz SA/NSA Bands: n2/n5/n7/n12/n25/n41/n48/n66/n71/n77/n78 DL 4 × 4 MIMO: n2/n7/n25/n41/n48/n66/n77/n78 UL 2 × 2 MIMO: n41/n48/n77
LTE	LTE Category: Cat 19 LTE Bands: B2/B4/B5/B7/B12/B13/B17/B14/B25/B26/B29/B30/ B41/B42/B43/B46/B48/B66/B71 DL 4 × 4 MIMO: B1/B3/B7/B38/B40/B41/B42
UMTS	WCDMA Bands: -

- Power Supply: Input:110V-220V AC 50/60Hz
DC:12V/2.5A

- External Interface: 1 X 10/100/1000/2500Mbps RJ45 wan
1 X 10/100/1000Mbps RJ45 LAN
1 X RJ11 Port, 1 X SIM Slot, 1 X Typs-C USB 3.0 Port
1 X PWR Port

- Button: WiFi/WPS Button, Reset Hole, ON/OFF Button

- Antenna: Eight 3dBi 5G/LTE antennas
Four 3dBi WiFi antennas

- Dimensions: (110 x 110 x 190)mm
-

Software Features

- Internet Connection Type: 5G NR/LTE/UMTS/Ethernet WAN
- Function: Auto-APN
VoLTE, CSFB Voice
QoS
Guest Network
FOTA
Standard TR069
- DHCP: Server, DHCP Reservation, Static Route, DDNS
- Quality of Service: Download/Upload Speed control
- Port Forwarding: Virtual Server, Port Triggering, DMZ
- VPN: PPTP, L2TP
- Access Control: URL Filter
- Firewall Security: DoS, SPI Firewall, Port Filter, ACL Filter
- Management: Access Control
Local Management
Remote Management

Wireless

- Wireless Standard: 802.11b/g/n, 802.11ac, 802.11ax
- Wireless Speed: 2.4GHz: Up to 1148Mbps; 5GHz: Up to 2402Mbps
- Wireless Frequency: 2.4GHz, 5GHz
- Wireless Security: WEP, WPA2, WPA2 Mix, WPA3, WPA3 Transition

Environment

- Operating Temperature: 0°C~40°C(32°F~104°F)
- Storage Temperature: -40°C~70°C(-40°F~158°F)
- Relative Humidity: 10%~90%, non-condensing
- Storage Humidity: 5%~95%, non-condensing

Package Contents

- 1 x WR862GVNM Device
- 1 x Power Adapter
- 1 x RJ11 Cable
- 1 x RJ45 Cable
- 1 x Quick Installation Guide