


N300 Wireless Cat 4 LTE & VoLTE Router

WR624VL



 LTE

 VoLTE


 Qos

 Guest Network


 Bulit-in Firewall

Wiring free , Whenever and Wherever

With LTE Advanced signal coverage for best performance, WR624VL allows you to receive Internet access without cable and fiber. WR624VL, a mobile network solution is the best choice for remote areas such as suburban area, seller store, restuarant, rental housing, small and medium-sized companies, providing the access to the Internet wherever and whenever the user is located.



4G Mobile SIM + WR624VL = Access to the Internet Instantly




Specifications

Hardware

- Mobile Communication System: CN
 - FDD-LTE: B1/B3/B5/B8
 - TDD-LTE: B34/B38/B39/B40/B41
 - WCDMA: B1/B5/B8
 - GSM: B3/B8
- Link Speed Rate (Max.): FDD-LTE: 150Mbps(DL)/50Mbps(UL)
TDD-LTE: 130Mbps(DL)/30Mbps(DL)
- Power Supply: Input:110V-220V AC 50/60Hz
DC:12V/1A
- External Interface: 4 X 10/100Mbps RJ45 Ports, 1 X RJ11 Port
1 X SIM Slot, 1 X Micro-USB 2.0 Port
1 X PWR Port
- Button: WiFi/WPS Button
Reset Hole
ON/OFF Button
- Antenna: Two 5dBi LTE antennas
Two 5dBi WiFi antennas
- Dimensions: (202 x 128 x 35)mm

AU	EU
B1/B2/B3/B4/B5/B7/B8/B28/B66	B1/B3/B7/B8/B20/B28
B40	B38/B40/B41
B1/B2/B4/B5/B8	B1/B8
B2/B3/B5/B8	B3/B8



Software Features

- Internet Connection Type: FDD LTE/TDD LTE/UMTS/WCDMA/GSM
- Function: Auto-APN
VoLTE, CSFB Voice
QoS
Guest Network
FOTA
Standard TR069
- DHCP: Server, DHCP Reservation, Static Route, DDNS
- Quality of Service: Download / Upload Speed control
- Port Forwarding: Virtual Server, Port Triggering, DMZ
- VPN: PPTP, L2TP
- Access Control: URL Filter
- Firewall Security: DoS, SPI Firewall, Port Filter, ACL Filter
- Management: Access Control
Local Management
Remote Management

Wireless

- Wireless Standard: 802.11b/g/n
- Wireless Speed: 2.4GHz: Up to 300Mbps
- Wireless Frequency: 2.4GHz
- Wireless Security: WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Relative Humidity: 10%~90%, non-condensing
- Storage Humidity: 5%~95%, non-condensing

Package Contents

- 1 x WR624VL Device
- 1 x Power Adapter
- 1 x RJ11 Cable
- 1 x RJ45 Cable
- 1 x Quick Installation Guide