

Wired XGS-PON ONT With Voice


XP602XVR



10G LAN Port



Fiber Access



Qos



VoIP

Specifications

General

- GPON Standards: ITU-T G.9807
- Distance: 20Km Max
- Data Rates: Upstream: 10Gbps, Downstream: 10Gbps

Hardware

- Interfaces: 1 x SC/APC GPON Port, 1 x 10GE Port, 1 x GE Port, 1 POTS Port
- Buttons: Power ON/OFF Button, Reset Button
- Power Supply: DC 12V 1A
- Dimensions (W X D X H): 90*73*25.2mm

Software Features

- Quality of Service: WMM, Bandwidth Control
- Port Forwarding: L2/L3 forwarding, L3 NAPT
- VPN: 802.1Q tag VLAN, VLAN transparent mode/VLAN translation mode/VLAN trunk mode
- Access Control: Local Management Control, Host List, Access Schedule, Rule Management
- Firewall Security:
 - DoS, SPI Firewall
 - IP Address Filter/MAC Address Filter/Domain Filter
 - IP and MAC Address Binding
- Management: Access Control, Local Management, Remote Management

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Relative Humidity: 10%~90%, non-condensing
- Storage Humidity: 5%~95%, non-condensing

Package Contents

- 1 x XGS-PON ONT
- 1 x Power Adapter
- 1 x RJ45 Cable

Certifications

- CE, RoHS

